Application No.: 10/535,178

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the

application:

LISTING OF CLAIMS:

1. (currently amended): A portable shoehorn which is a shoehorn obtained by

bending a plate member, which has been bent in a breadth direction thereof, in a longitudinal

direction thereof approximately like a long bow to form a slender plate shape and whose grip

section is constituted so as to be folded into two parts at a central portion thereof to reduce an

entire length of the shoehorn approximately by half, wherein

a backscratcher is formed at a distal end of the grip section and an elastic body for

patting a human body is constituted so as to be removeably mounted to a portion of the

backscratcher and a shoehorn portion of the shoehorn.

2. (currently amended): A portable shoehorn which is a shoehorn obtained by bending a

plate member, which has been bent in a breadth direction thereof, in a longitudinal direction

thereof approximately like a long bow to form a slender plate shape and whose grip section is

constituted so as to be folded into two parts at a central portion thereof to reduce an entire length

of the shoehorn approximately by half, wherein

a backscratcher is formed at a distal end of the grip section and an elastic body for patting

a human body is constituted so as to be removeably mounted to a portion of the backscratcher

and a shoehorn portion of the shoehorn,

wherein the grip section is formed such that the breadth thereof is shorter than those of

the backscratcher and the shoehorn portion of the shoehorn, and the elastic body for patting a

human body comprises a main body portion with a spherically formed face contacting with a

2

Application No.: 10/535,178

human body and a mounting portion which is applied to be mounted to the backscratcher and the

shoehorn portion of the shoehorn; and

the mounting portion of the shoehorn of the elastic body for patting a human body is

formed with an engagement groove with a groove breadth which allows engagement with the

backscratcher and the shoehorn portion of the shoehorn without allowing engagement with the

grip section.

3. (previously presented): A portable shoehorn according to claim 1, wherein the

backscratcher is constituted with a corrugated projection provided at a bent end formed by

bending a distal end thereof and a plurality of small projections provided in a projecting manner

at left and right side edges near the bent portion; and

the engagement groove of the elastic body for patting a human body is formed with

engagement holes engaged with the small projections of the backscratcher.

4. (currently amended): A portable shoehorn comprising:

a bent plate member, said member comprising a grip section and a shoehorn section, each

of said grip section and said shoehorn section (1) being bent in a breadth-wise direction thereof

and in a longitudinal direction thereof approximately like a long bow to form a slender plate

shape, (2) having a distal end and a proximal end at which said sections are rotatably joined to

form a central portion, and (3) being foldable into two parts at said central portion to reduce an

entire length of the shoehorn approximately by half,

a backscratcher formed at the distal end of the grip section and a shoehorn formed at the

distal end of the shoehorn section, and

an elastic body for patting a human body, said elastic body comprising a main body

portion and a mounting portion, said mounting portion being operative for removeable mounting

of the elastic body to at least one of the grip section and the shoehorn section.

3

Application No.: 10/535,178

5. (currently amended): A portable shoehorn according to claim 4-A portable

shoehorn comprising:

a bent plate member, said member comprising a grip section and a shochorn section, each of said grip section and said shochorn section (1) being bent in a breadth-wise direction thereof and in a longitudinal direction thereof approximately like a long bow to form a slender plate shape. (2) having a distal end and a proximal end at which said sections are rotatably joined to form a central portion, and (3) being foldable into two parts at said central portion to reduce an entire length of the shochorn approximately by half.

a backscratcher formed at the distal end of the grip section and a shoehorn formed at the distal end of the shoehorn section, and

an elastic body for patting a human body, said elastic body comprising a main body portion and a mounting portion, said mounting portion being operative for removeable mounting of the elastic body to at least one of the grip section and the shochorn section.

wherein the mounting portion of said elastic body is shaped with an engagement groove to fit over and securely engage edges at a bend in the breadthwise direction of at least one of the grip portion and the shoehorn portion.

6. (currently amended): A—portable—shoehorn—according—to—claim—4—A portable shoehorn comprising:

a bent plate member, said member comprising a grip section and a shoehorn section, each of said grip section and said shoehorn section (1) being bent in a breadth-wise direction thereof and in a longitudinal direction thereof approximately like a long bow to form a slender plate shape, (2) having a distal end and a proximal end at which said sections are rotatably joined to form a central portion, and (3) being foldable into two parts at said central portion to reduce an entire length of the shoehorn approximately by half.

Application No.: 10/535,178

a backscratcher formed at the distal end of the grip section and a shoehorn formed at the

distal end of the shoehorn section, and

an elastic body for patting a human body, said elastic body comprising a main body

portion and a mounting portion, said mounting portion being operative for removeable mounting

of the elastic body to at least one of the grip section and the shoehorn section,

wherein the mounting portion of said elastic body is shaped with an engagement groove

to fit over and securely engage edges at a bend in the breadthwise direction of both the grip

portion and the shoehorn portion.

5